

# LaserPlus: AC Power Supply Module (LP-PS-AC)

## 1 GHz HIGH DENSITY COMPACT CATV OPTICAL TRANSMISSION SYSTEM

### Features / Benefits

- Automatic sensing of input AC voltage (90-264 V<sub>AC</sub>) for ease-of-installation
- IEC power connector ensures worldwide power cord availability
- Each chassis requires one power supply to provide +5 V<sub>DC</sub> to application modules
- Each chassis accepts a second optional power supply for hot failsafe backup
- Mix-and-match AC and/or DC modules in the same chassis for maximum redundancy
- Power supplies are fully isolated, eliminating single source of power failure
- Front Panel status LEDs: Power, Chassis Temperature, Summary Alarm for modules
- Single-slot width, plug-in, front-access design features hot-swap module capability
- Chassis-based plenum with four large fans creates more airflow & better reliability than module-based fans; if fan failure occurs, power supply remains in operation



### Specifications

#### ELECTRICAL, ENVIRONMENTAL & MECHANICAL PARAMETERS:

Dimensions	4.5" H x 1.125" W x 8.75" D (11.4 cm x 2.9 cm x 22.2 cm)
Weight (Empty)	1 lb (0.454 kg)
Operating Temperature Range	0°C to +50°C (+32°F to +122°F) (Air temperature measured at air inlet of <i>Model LP-CH</i> chassis)
Humidity Range	to 95% non-condensing (Recommended for use only in non-condensing environments)
Mounting	<i>Model LP-CH-16 LaserPlus</i> Chassis
Module Slots	One slot width: #16=power supply; #15=apps or redundant PS
Powering	Output: 5.25V <sub>DC</sub> per applications module @ 21A max; Input: Universal 90-264 V <sub>AC</sub> @ 47-63 Hz < 150 Watts
Protection	3AG 250V 3.25A SB fuse [Littelfuse PN# 31303.2]

#### POWER SUPPLY INTERFACES:

Input Connector	<i>Model LP-PS</i> : IEC power connector
Status Interface	(Functions Monitored) DC Voltages, Internal temperature LED Indicators (Green/Red) Voltage Presence; Temperature Alarm; Slots 1-16 Summary Alarm

*All specifications are subject to change without notice*