

## Booster EDFA - Model OTEB-CO-B Series

### Features and Benefits

#### Compact high performance 1RU 19" EDFA

Specifically for distribution of 1550nm CATV/video/data in HFC, PON/AON or FTTH systems

Typically used in a launch or mid-span application. Optimized for use with Olson fiber-based DCM.

Low optical input level requirements with excellent low noise performance at high output

90-254 Volts AC power supply. DC option not available.

Optional SNMP monitoring.

1540nm to 1560nm wavelength range

LED indicators and LCD display for easy setup and maintenance.

Single, dual and quad optical output options

SC/APC optical connector standard.



The Olson Technology Model OTEB-CO-B Series Booster EDFA incorporates reliable optical output drive circuitry, and laser TEC (Thermo-Electric Cooler) to provide a highly reliable Erbium-Doped Optical Amplifier. Built-in microprocessor software allows the user to monitor a number of system parameters, including: laser status, systems alarm, network management, and TEC circuit operation. If a critical problem is detected, the power supply for the laser will shut down automatically, a red LED indicator will light, and the front panel display will show the nature of the problem. Optional SNMP network management is available through the RJ45 interface. The EDFA is housed in a 1RU 19" rack mount configuration with an integrated 90-254 Volts AC power supply. The pump laser is controlled by a front panel key switch that can only be removed in the "Off" position to prevent tampering.

This rugged, low-profile, high-efficiency EDFA design utilizes highly reliable pump lasers for maximum reliability. The unit accepts a very wide optical input range (-10dBm to +10dBm) and provides a total composite/saturated output power from +13dBm to +26dBm, depending on the specific model. The *LaserLite* Model OTEB-CO-B Series erbium doped fiber amplifier is the perfect companion to the Olson *LaserPlus* and *LaserLite* families of 1550nm EM and DM transmitters and *MetroNode* and *PremiseNode* families of receiver/nodes. It is also designed to operate seamlessly with optical transmitters, receivers and nodes from most leading manufacturers.



# Booster Optical Amplifier

## System Specifications

### Optical Characteristics (with SM 9/125µm Fiber)

	Min	Typ	Max	Units
Optical Output Power (Total)*	+13		+26	dBm
Optical Input Power	-10	+3	+10	dBm
Wavelength	1540		1560	nm
Output Stability		±0.3		dB
Noise Figure (0dBm in)		5.0	6.3	dB
Noise Figure (+6dBm in)		6.0		dB
Pump Power Leakage			-30	dBm
Reflection Loss			-40	dB
Optical Connector	SC/APC			
SNMP Network Management Interface **	RJ45			
Communication Interface	RS-232			

\* With 0dBm optical input



\*\* SNMP is optional at the time of ordering

### Electrical and Environmental Characteristics

	Min	Typ	Max	Units
AC Power Supply Voltage	90		254	V <sub>AC</sub>
DC Power Supply Voltage		-48		V <sub>DC</sub>
Operating Temp. Range	0		+50	°C
Storage Temp. Range	-20		+65	°C
Humidity (Non condensing)	5		90	%

### Physical Characteristics

	Min	Typ	Max	Units
Weight		12		lb.
		5.5		kg
Dimensions (W x L x H)	19	14.5	1.75	in.
	483	368	44	mm



### Ordering Information

Model OTEB-CO-B113-yy-pp-z/S	EDFA, 1 Output, +13dBm Optical Output per Port
Model OTEB-CO-B114-yy-pp-z/S	EDFA, 1 Output, +14dBm Optical Output per Port
Model OTEB-CO-B115-yy-pp-z/S	EDFA, 1 Output, +15dBm Optical Output per Port
Model OTEB-CO-B116-yy-pp-z/S	EDFA, 1 Output, +16dBm Optical Output per Port
Model OTEB-CO-B117-yy-pp-z/S	EDFA, 1 Output, +17dBm Optical Output per Port
Model OTEB-CO-B118-yy-pp-z/S	EDFA, 1 Output, +18dBm Optical Output per Port
Model OTEB-CO-B119-yy-pp-z/S	EDFA, 1 Output, +19dBm Optical Output per Port
Model OTEB-CO-B120-yy-pp-z/S	EDFA, 1 Output, +20dBm Optical Output per Port
Model OTEB-CO-B121-yy-pp-z/S	EDFA, 1 Output, +21dBm Optical Output per Port
Model OTEB-CO-B122-yy-pp-z/S	EDFA, 1 Output, +22dBm Optical Output per Port
Model OTEB-CO-B123-yy-pp-z/S	EDFA, 1 Output, +23dBm Optical Output per Port
Model OTEB-CO-B124-yy-pp-z/S	EDFA, 1 Output, +24dBm Optical Output per Port
Model OTEB-CO-B221-yy-pp-z/S	EDFA, 2 Outputs, +21dBm Optical Output per Port
Model OTEB-CO-B419-yy-pp-z/S	EDFA, 4 Outputs, +19dBm Optical Output per Port

Where

yy	Optical connector type; SA = SC/APC (Standard), FA = FC/APC (Optional)
pp	Power; AC = AC power (universal AC), DC = DC power (48VDC)
z	Optical Connector Position (F = Front, B = Back)
/S	Designates unit with SNMP. Omit for no SNMP